



CVE08

CODE		M.U.	CVE08002208000		CVE08002288000		CVE08U12208000		CVE08U12038000
UL Listed			--		--		✓		✓
Rated Voltage		V, ~	230, 1		400, 2	460, 2	230, 1		115, 1
Nominal Frequency		Hz	50	60	50	60	50	60	60
Cooling Capacity	L35L35	W	850	900	800	850	--	900	900
Cooling Capacity	L35L50	W	620	700	600	650	--	700	700
Power Consumption	L35L50	W	420	600	420	600	--	600	600
Current Compsuntion	CE, L35L35	A	2,6	2,7	1	1,4	2,6	2,7	--
	UL,L45L55	A	--		--		--	3,9	7,2
Start-up Current	CE	A	20		20		20		--
Internal operating temperatures	min/max	°C	+25 / +45		+25 / +45		+25 / +45		+25 / +45
External operating temperatures	min/max	°C	+20 / +55		+20 / +55		+20 / +55		+20 / +55
Internal Circuit Protection Degree	CE	IP	54		54		54		--
	UL	Type	--		--		--	12	12
External Sound Pressure		dB(A)	64		64		64		64
Height (A)		mm	642		642		642		642
Width (B)		mm	314,5		314,5		314,5		314,5
Depth (C)		mm	221		221		221		221
Weight		kg	27		30		27		27