



CVE11

CODE		M.U.	CVE11002208000		CVE11002288000		CVE11U12208000		CVE11U12038000
UL Listed			--		--		✓		✓
Rated Voltage		V, ~	230, 1		400, 2	460, 2	230, 1		115, 1
Nominal Frequency		Hz	50	60	50	60	50	60	60
Cooling Capacity	L35L35	W	1100	1150	1050	1100	--	1150	1150
Cooling Capacity	L35L50	W	840	890	790	840	--	890	890
Power Consumption	L35L50	W	590	750	510	650	--	750	650
Current Compsuntion	CE, L35L35	A	2,8	3,3	1,3	1,4	2,8	3,3	--
	UL, L45L55	A	--		--		--	3,6	7,5
Start-up Current	CE	A	20		40		20		--
Internal operating temperatures	min/max	°C	+25 / +45		+25 / +45		+25 / +45		+25 / +45
External operating temperatures	min/max	°C	+20 / +55		+20 / +55		+20 / +55		+20 / +55
Internal Circuit Protection Degree	CE	IP	54		54		54		--
	UL	Type	--		--		--	12	12
External Sound Pressure		dB(A)	65		65		65		65
Height (A)		mm	913		913		913		913
Width (B)		mm	413		413		413		413
Depth (C)		mm	248		248		248		248
Weight		kg	44		50		44		44