



CVE15

CODE		M.U.	CVE15002208000		CVE15002288000		CVE15U12208000		CVE15U12038000	CVE15U12628000	
UL Listed			--		--		✓		✓	✓	
Rated Voltage		V, ~	230, 1		400, 2	460, 2	230, 1		115, 1	400, 3	460, 3
Nominal Frequency		Hz	50	60	50	60	50	60	60	50	60
Cooling Capacity	L35L35	W	1500	1600	1400	1500	--	1600	1600	--	1500
Cooling Capacity	L35L50	W	1200	1280	1150	1200	--	1280	1280	--	1200
Power Consumption	L35L50	W	750	825	750	825	--	825	825	--	830
Current Compsuntion	CE, L35L35	A	3,9	4,3	2,5	2,6	3,9	4,3	--	--	1,4
	UL, L45L55	A	--		--		--	4,5	9,4 L40L50	--	1,97
Start.-up Current	CE	A	28		110		28		--	31	
Internal operating temperatures	min/max	°C	+25 / +45		+25 / +45		+25 / +45		+25 / +40	+25 / +45	
External operating temperatures	min/max	°C	+20 / +55		+20 / +55		+20 / +55		+20 / +50	+20 / +55	
Internal Circuit Protection Degree	CE	IP	54		54		54		--	54	
	UL	Type	--		--		--	12	12	--	12
External Sound Pressure		dB(A)	65		65		65		65	65	
Height (A)		mm	913		913		913		913	1005	
Width (B)		mm	413		413		413		413	413	
Depth (C)		mm	248		248		248		248	263	
Weight		kg	46		53		46		46	48	