



CVO40

CODE		M.U.	CVO40002208000		CVO40002618000		CVO40U12208000		CVO40U12628000	
UL Listed			--		--		✓		✓	
Rated Voltage		V, ~	230,1		400,3	460,3	230,1		400,3	460,3
Nominal Frequency		Hz	50	60	50	60	50	60	50	60
Cooling Capacity	L35L35	W	4000	4100	3950	4050	-	4100	-	4050
Cooling Capacity	L35L50	W	3000	3300	2960	3260	-	3300	-	3260
Power Consumption	L35L50	W	1730	1950	1730	1950	-	1850	-	1840
Current Compsuntion	CE L35L35	A	8,2	9,4	2,9	4	2,3	7,3	2,8	3,1
	UL L45L55	A	-		-		-	8,3	-	5,26
Start.-up Current	CE	A	42		25		36		19	
Internal operating temperatures	min/max	°C	+25 / +45		+25 / +45		+25 / +45		+25 / +45	
External operating temperatures	min/max	°C	-20 / +55		-20 / +55		-40 / +55		-40 / +55	
Internal Circuit Protection Degree	CE	IP	54		54		55		55	
	UL	Type	-		-		-	4	-	4
External Sound Pressure		dB(A)	67		67		67		67	
Height (A)		mm	1211		1211		1211		1211	
Width (B)		mm	514		514		514		514	
Depth (C)		mm	370		370		370		370	
Weight		kg	80		85		80		85	