



LED PILOT LIGHT Ø22

DESCRIPTION	POWER SUPPLY	CODE	WEIGHT gramm	MIN. PACK QUANTITY	SIZES
SINGLE LED INDICATOR X1—X2	AC/DC 6V 1	PLML 2 L6	15	10	
	AC/DC 12V 1	PLML 2 L12	15	10	
	AC/DC 24V	PLML 2 L24	15	10	
	AC/DC 48V	PLML 2 L48	15	10	
	AC/DC 110V	PLML 2 L110	15	10	
	AC/DC 220V	PLML 2 L220	15	10	
	AC 380V 1	PLML 2 L380	15	10	

COMPLY WITH RULES		EN60947-5-1 / GB14048.5	DIAGRAM
Operational temperature	°C	-5 +40	RESISTANCE
Operational humidity		45% ... 90%	
AC rated frequency	Hz	50/60	CAPACITY RESISTANCE
Rated insulation voltage	1 min V	2500V	
Over voltage category	EN60947.1	III	AC 220 ... 380V
Pollution grade	EN60947.1	3	
Protection degree	EN60529	IP65, IP2X terminals	
Connection:			
Terminal block caliber		A2	
Terminal screw		M3,5	
Flexible and solid conductor section	min/max	n. 1 1/2,5 mm² - n. 2 1/2,5 mm²	
Rated operational voltage Ue	AC/DC V	6, 12, 24, 48, 110, 220	
	AC V	380	
Rated operational voltage Ie	mA	≤80 6,12V	
	mA	≤20 24, 48, 110, 220, 380V	
Electrical life	h	≥30.000	
Brightness	cd/m²	100	
Mounting	mm	Ø22,5	

MULTIFUNCTION PUSH BUTTONS Ø22 | NOT LIGHT

TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
DUAL PUSH BUTTON		PPDN	38	10	
		PPDN	38	10	

TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
EXTENDED DUAL PUSH BUTTON		PPDNR	38	10	
		PPDNR.3	38	10	

TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
MULTIFUNCTION PUSH BUTTON		PPMN	40	10	

MULTIFUNCTION PUSH BUTTONS Ø22 | LIGHT

TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
DUAL PUSH BUTTON		PPDL	30	10	
		PPDL.1	30	10	

TYPE	COLOUR INDEX	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
EXTENDED DUAL PUSH BUTTON		PPDLR	30	10	
		PPDLR.3	30	10	