

LEDLAMP CP22

COMPACT, HIGH EFFICIENCY ENCLOSURE LED LAMP

Fitted with Schuko socket and switch, it can be mounted with clips on DIN rail, on a bracket (ALFASTAFF) with screws or with magnetic fixing. It fits exactly one 19" height/unit (44 mm).




FEATURES	Unit	LEDLAMPCP22	LEDLAMPSP22
Power supply	V Hz	230 50/60	230 50/60
Schuko socket	-	Yes 6A	No
Luminosity	Lm	900	
Lamp type	-	LED	
Power consumption	W	6	
Service life	hrs	30000	
Switch	-	On/Off for the lamp only	
Connection	-	3-pole terminal for 1.5 mm ² wire	
Casing	-	Aluminium profile and ABS, UL94 V0, light grey	
Protection degree EN60529	-	IP20	
Protection class	-	Class I, earthed	
Operating temperature	°C(°F)	-20 / +50 (-4 / +122)	
Storage temperature	°C(°F)	-45 / +80 (-49 / +176)	
Mounting	-	Clip on DIN rail, magnet or bracket, see ordering code below	
Installation position	-	variable	
Dimensions HxWxD	mm	95x43x277	
Weight (with packaging)	kg	0.39 (0.47)	
Package dimensions HxWxD	mm	105x58x310	
Conformity/Certifications	-	CE	

Versions

Clip mounting on DIN rail	LEDLAMPCP22+CLIP	LEDLAMPSP22+CLIP
Magnet mounting	LEDLAMPCP22+MAGN	LEDLAMPSP22+MAGN
Bracket mounting	LEDLAMPCP22+STAF	LEDLAMPSP22+STAF

Accessories

Bracket for lamp	ALFASTAFF	ALFASTAFF
Magnet for lamp	ALFAMAGNETE	ALFAMAGNETE
Door limit switch without block	FINCOR	FINCOR
Door limit switch	FINRIP	FINRIP
Safety flashing device with lamp switch	FSL	FSL
Safety flashing device with lamp and auxiliary switches	FSLA	FSLA



Specifications, values and drawings are subject to change without notice.