


|                        |                                                                                                                                                                                                                                                                                                                  |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>8015-6v</b>                                                                                                                                                                                                                                                                                                   |
| article description    | <b>CEE angled plug 16A 5p 6h IP44 TWIST</b>                                                                                                                                                                                                                                                                      |
| description long       | CEE angled plug 16A 5p 6h IP44 TWIST<br>housing material: PC/ABS<br>rated current: 16A<br>number of poles: 5 (3P+N+PE)<br>clock-position: 6h<br>rated voltage/frequency: 200/346V~ - 240/415V~ / 50+60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>IP protection class: IP44 |
| GTIN (EAN)             | 9003399079894                                                                                                                                                                                                                                                                                                    |
| country of origin      | AT                                                                                                                                                                                                                                                                                                               |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                         |
| net weight             | 0.155 kg                                                                                                                                                                                                                                                                                                         |
| packaging quantity     | 10                                                                                                                                                                                                                                                                                                               |
| minimum order quantity | 10                                                                                                                                                                                                                                                                                                               |

|                                 |                      |
|---------------------------------|----------------------|
| ETIM 10.0                       | EC000140             |
| IEC-amperage                    | 16 A                 |
| Number of poles                 | 5                    |
| Voltage according to EN 60309-2 | 400 V (50+60 Hz) red |
| Clock hour position             | 6 h                  |
| Identification colour           | Red                  |
| Degree of protection (IP)       | IP44                 |
| Connection system               | Screwed terminal     |
| Cable entry                     | Gland nut            |
| Suitable for cable diameter     | 8 – 16 mm            |
| Angle of plug                   | Angled               |
| Material                        | Plastic              |
| Contact material                | CuZn                 |
| Surface treatment contacts      | Nickel-plated        |

|                        |                       |
|------------------------|-----------------------|
| a                      | 107 mm                |
| b                      | 71 mm                 |
| c                      | 61 mm                 |
| d                      | 102 mm                |
| e                      | 20 °                  |
| K (cable Ø)            | 8-16 mm               |
| SW                     | 42 mm                 |
| wire flexible          | 1-2,5 mm <sup>2</sup> |
| contact screws         | 100 Ncm               |
| strain relief          | 500 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 10-12 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |



<https://www.pceelectric.at/shop/en/?func=detail&artnr=8015-6v>

