

ONTEC S M2 302 M ST W TM-OS.M2STM360W

Click on the selected icon to download the file:



No: 1026



No: 4662/2022
Valid until:
02.06.2027



No: 88-139797



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030




No: 1026



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 1026



No: V1





No: V3.0



Producer	TM TECHNOLOGIE
Application	anti-panic lighting
Family	ONTEC S
Colour/Colour - RAL	white , RAL9003
Version	standard
Operating mode	M
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	241 lm
Light source	LED
Maximum light power	4.7 W
Active power	6.5 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah

Warranty (body, electronics, light source)	24 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm





2,5	3,5	9,5	3,5	9,5
3	3,5	10,5	3,5	10,5
4	4	12	4	12
5	4	13,5	4	13,5
6	4	14,5	4	14,5
7	4	15,5	4	15,5
8	4	16	4	16
9	4	16,5	4	16,5
10	3,5	17	3,5	17

$E_{min} \geq 0,5 \text{ lx}$