

# ONTEC S M1 180 M ST W TM-OS.M1STM860W

Click on the selected icon to download the file:



No: 1026



No: 4662/2022  
Valid until:  
02.06.2027



No: 88-139797



No:  
B\_BK\_60112\_0426\_2024  
Valid until:  
24.01.2030



No: 1026



No: 2291559.02-  
UAE  
Valid until:  
05.11.2026



No: 1026




No: V1




No: V3.0



|                                            |                                                                      |
|--------------------------------------------|----------------------------------------------------------------------|
| Producer                                   | <b>TM TECHNOLOGIE</b>                                                |
| Application                                | <b>anti-panic lighting</b>                                           |
| Family                                     | <b>ONTEC S</b>                                                       |
| Colour/Colour - RAL                        | <b>white , RAL9003</b>                                               |
| Version                                    | <b>standard</b>                                                      |
| Operating mode                             | <b>M</b>                                                             |
| Duration time                              | <b>3 h</b>                                                           |
| Protection degree                          | <b>IP65</b>                                                          |
| Impact protection degree                   | <b>IK08</b>                                                          |
| Appliance classes                          | <b>II</b>                                                            |
| Material                                   | <b>plastic</b>                                                       |
| Installation method*                       | <b>surface, flush-mounted, suspended, wall, ceiling, at an angle</b> |
| Luminous flux emergency                    | <b>150 lm</b>                                                        |
| Light source                               | <b>LED</b>                                                           |
| Maximum light power                        | <b>2.5 W</b>                                                         |
| Active power                               | <b>3.3 W</b>                                                         |
| Nominal voltage AC                         | <b>210-250 V</b>                                                     |
| LED lifetime                               | <b>50000 h</b>                                                       |
| Colour temperature                         | <b>5700 K</b>                                                        |
| Minimum temperature                        | <b>+ 0 °C</b>                                                        |
| Maximum temperature                        | <b>+40 °C</b>                                                        |
| Battery                                    | <b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b>                                 |
| Warranty (body, electronics, light source) | <b>24 months</b>                                                     |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>272 mm x 40 mm x 144 mm</b>                                       |





|     |     |      |     |      |
|-----|-----|------|-----|------|
| 2,5 | 3   | 8,5  | 3   | 8,5  |
| 3   | 3,5 | 9    | 3,5 | 9    |
| 4   | 3,5 | 10,5 | 3,5 | 10,5 |
| 5   | 3,5 | 11,5 | 3,5 | 11,5 |
| 6   | 3   | 12,5 | 3   | 12,5 |
| 7   | 3   | 13   | 3   | 13   |
| 8   | 3   | 13,5 | 3   | 13,5 |
| 9   | 2   | 14   | 2   | 14   |
| 10  | 3   | 13   | 3   | 13   |

$E_{min} \geq 0,5 \text{ lx}$