

ONTEC S M1 180 M AT W TM-OS.M1ATM860W

Click on the selected icon to download the file:



No: 1026



No: 4662/2022
Valid until:
02.06.2027



No: 88-139797



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030




No: 1026



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 1026



No: V1







No: V3.0



Producer	TM TECHNOLOGIE
Application	anti-panic lighting
Family	ONTEC S
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	M
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	150 lm
Light source	LED
Maximum light power	2.5 W
Active power	3.3 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah

Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm





2,5	3	8,5	3	8,5
3	3,5	9	3,5	9
4	3,5	10,5	3,5	10,5
5	3,5	11,5	3,5	11,5
6	3	12,5	3	12,5
7	3	13	3	13
8	3	13,5	3	13,5
9	2	14	2	14
10	3	13	3	13

$E_{min} \geq 0,5 \text{ lx}$