

ONTEC S20 M1U 60 NM ST W IP65 TM-S2.MUSTN160W

Click on the selected icon to download the file:



No: 1626



No: 6074/2026
Valid until:
15.04.2031



No: 88-129369



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1626



No:
2291559.02.UAE
Valid until:
05.11.2026



No: 1626



No: V1





No: V3.0






Producer	TM TECHNOLOGIE
Application	anti-panic lighting, evacuation route direction
Family	ONTEC S20
Colour/Colour - RAL	white , RAL9003
Version	standard
Operating mode	NM
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux	>2 cd/m ²
Luminous flux emergency	125 lm
Light source	LED
Maximum light power	0.9 W
Active power	2.0 W
Nominal voltage AC	210-250 V
LED lifetime	100000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah

Warranty (body, electronics, light source)	24 months
Net dimensions L x W x H [±2 mm]	227 mm x 40 mm x 120 mm





				
2,5	3	7	3	7
3	3	8	3	8
4	3	9,5	3	9,5
5	3,5	10,5	3,5	10,5
6	3,5	11,5	3,5	11,5
7	3,5	12	3,5	12
8	2,5	13	2,5	13
9	2	13,5	2	13,5
10	1,5	13,5	1,5	13,5

$E_{min} \geq 0,5 \text{ lx}$