

ITECH M2 302 M AT B

TM-IT.M2ATM360B

Click on the selected icon to download the file:



No: 0926



No: 4570/2022
Valid until:
10.04.2027



No: 88-137960




No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0926



No: 0926



No: V1




No: V2.12




Producer	TM TECHNOLOGIE
Application	anti-panic lighting
Family	ITECH
Colour/Colour - RAL	black , RAL9005
Version	autotest
Operating mode	M
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	270 lm
Light source	LED
Maximum light power	2 W
Active power	6.4 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah

Warranty (body, electronics, light source) **36 months**

Net dimensions **H x Ø [±2 mm]** **74 mm x 171 mm**



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	3,5	10	3,5	10
3	4	11	4	11
4	4	12,5	4	12,5
5	4	14	4	14
6	4,5	15,5	4,5	15,5
7	4	16	4	16
8	4	16,5	4	16,5
9	5	16	5	16
10	5	16	5	16

$E_{min} \geq 0,5 \text{ lx}$