

ITECH M1 60 NM ST W

TM-IT.M1STN660W

Click on the selected icon to download the file:



No: 0926



No: 4570/2022
Valid until:
10.04.2027



No: 88-137960




No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0926




No: 0926



No: V1




No: V2.12




Producer	TM TECHNOLOGIE
Application	anti-panic lighting
Family	ITECH
Colour/Colour - RAL	white , RAL9003
Version	standard
Operating mode	NM
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	389 lm
Light source	LED
Maximum light power	2 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah

Warranty (body, electronics, light source) **24 months**

Net dimensions **H x Ø [±2 mm]** **74 mm x 171 mm**



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	3,5	11	3,5	11
3	4	12	4	12
4	4,5	13,5	4,5	13,5
5	5	15	5	15
6	5	16,5	5	16,5
7	4,5	17,5	4,5	17,5
8	4,5	18,5	4,5	18,5
9	4,5	19	4,5	19
10	4	19,5	4	19,5

$E_{min} \geq 0,5 \text{ lx}$