TM TECHNOLOGIE

ITECH M1 60 NM AT W
TM-IT.M1ATN660W

Click on the selected icon to download the file:

No: 0926

No: 4570/2022
Valid until:
10.04.2027

No: 88-137960


No:
B_BK_60112_0422_2024
Valid until:
24.01.2030

No: 0926


No: 0926

No: V1


No: V2.12



Producer	**TM TECHNOLOGIE**
Application	**anti-panic lighting**
Family	**ITECH**
Colour/Colour - RAL	**white , RAL9003**
Version	**autotest**
Operating mode	**NM**
Duration time	**1 h**
Protection degree	**IP65**
Impact protection degree	**IK06**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, suspended, ceiling, at an angle**
Luminous flux emergency	**389 lm**
Light source	**LED**
Maximum light power	**2 W**
Active power	**1.2 W**
Nominal voltage AC	**210-250 V**
LED lifetime	**50000 h**
Colour temperature	**5700 K**
Minimum temperature	**+ 0 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**36 months**
Net dimensions **H x Ø** [±2 mm]	**74 mm x 171 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	3,5	11	3,5	11
3	4	12	4	12
4	4,5	13,5	4,5	13,5
5	5	15	5	15
6	5	16,5	5	16,5
7	4,5	17,5	4,5	17,5
8	4,5	18,5	4,5	18,5
9	4,5	19	4,5	19
10	4	19,5	4	19,5

Emin ≥ 0,5 lx