

ONTEC C M1 180 NM ST B TM-OC.M1STN800B

Click on the selected icon to download the file:



No: 0126



No: 4397/2021
Valid until:
11.09.2026



No: 88-128463
Valid until:
25.05.2026



No:
B_BK_60112_0424_2024
Valid until:
24.01.2030



No: 0126



No: 2291559.02-
UAE
Valid until:
05.11.2026




No: 0126




No: V1







No: V1.14



Producer	TM TECHNOLOGIE
Application	anti-panic lighting
Family	ONTEC C
Colour/Colour - RAL	black , RAL9005
Version	standard
Operating mode	NM
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Installation method*	flush-mounted, ceiling
Luminous flux emergency	167 lm
Light source	LED
Maximum light power	3 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	24 months
Net dimensions H x Ø [±2 mm]	14 mm x 90 mm





2,5	3	7,5	3	7,5
3	3,5	8,5	3,5	8,5
4	4	10	4	10
5	4,5	11,5	4,5	11,5
6	4	13	4	13
7	3,5	14	3,5	14
8	2,5	15	2,5	15
9	2,5	15	2,5	15
10	2	15	2	15

$E_{min} \geq 0,5 \text{ lx}$