

ONTEC D M1 60 NM AT B

TM-OD.M1ATN600B

Click on the selected icon to download the file:



No: 0126



No: 4397/2021
Valid until:
11.09.2026



No: 88-128463



No:
B_BK_60112_0424_2024
Valid until:
24.01.2030



No: 0126



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 0126



No: V1








No: V1.14



Producer	TM TECHNOLOGIE
Application	anti-panic lighting
Family	ONTEC D
Colour/Colour - RAL	black , RAL9005
Version	autotest
Operating mode	NM
Duration time	1 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Installation method*	flush-mounted, ceiling
Luminous flux emergency	338 lm
Light source	LED
Maximum light power	2.4 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah

Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	90 mm x 90 mm x 14 mm





2,5	3,5	8	3,5	8
3	4	9	4	9
4	5	11	5	11
5	5,5	13	5,5	13
6	5,5	15	5,5	15
7	6	16,5	6	16,5
8	6	18	6	18
9	5,5	19	5,5	19
10	5	20	5	20

$E_{min} \geq 0,5 \text{ lx}$