

# ONTEC R M1 60 NM ST B

## TM-OR.M1STN600B

Click on the selected icon to download the file:



No: 0426



No: 4410/2021  
Valid until:  
04.09.2026



No: 88-128814



No:  
B\_BK\_60112\_0424\_2024  
Valid until:  
24.01.2030




No: 0426



No: 2291559.02-  
UAE  
Valid until:  
05.11.2026




No: 0426




No: V1







No: V3.0



|                                            |                                                           |
|--------------------------------------------|-----------------------------------------------------------|
| Producer                                   | <b>TM TECHNOLOGIE</b>                                     |
| Application                                | <b>anti-panic lighting</b>                                |
| Family                                     | <b>ONTEC R</b>                                            |
| Colour/Colour - RAL                        | <b>black , RAL9005</b>                                    |
| Version                                    | <b>standard</b>                                           |
| Operating mode                             | <b>NM</b>                                                 |
| Duration time                              | <b>1 h</b>                                                |
| Protection degree                          | <b>IP20</b>                                               |
| Impact protection degree                   | <b>IK03</b>                                               |
| Appliance classes                          | <b>II</b>                                                 |
| Material                                   | <b>plastic</b>                                            |
| Installation method*                       | <b>surface, flush-mounted, wall, ceiling, at an angle</b> |
| Luminous flux emergency                    | <b>360 lm</b>                                             |
| Light source                               | <b>LED</b>                                                |
| Maximum light power                        | <b>2 W</b>                                                |
| Active power                               | <b>1.2 W</b>                                              |
| Nominal voltage AC                         | <b>210-250 V</b>                                          |
| LED lifetime                               | <b>50000 h</b>                                            |
| Colour temperature                         | <b>5700 K</b>                                             |
| Minimum temperature                        | <b>+10 °C</b>                                             |
| Maximum temperature                        | <b>+35 °C</b>                                             |
| Battery                                    | <b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b>                      |
| Warranty (body, electronics, light source) | <b>24 months</b>                                          |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>130 mm x 31 mm x 130 mm</b>                            |





|     |     |      |     |      |
|-----|-----|------|-----|------|
| 2,5 | 4   | 8,5  | 4   | 8,5  |
| 3   | 4   | 10   | 4   | 10   |
| 4   | 5   | 12,5 | 5   | 12,5 |
| 5   | 5,5 | 14,5 | 5,5 | 14,5 |
| 6   | 5,5 | 16,5 | 5,5 | 16,5 |
| 7   | 5   | 18   | 5   | 18   |
| 8   | 5   | 19   | 5   | 19   |
| 9   | 4,5 | 20   | 4,5 | 20   |
| 10  | 4   | 20,5 | 4   | 20,5 |

$E_{min} \geq 0,5 \text{ lx}$