

ONTEC G E1E 180 M AT B TM-OG.EEATM800B

Click on the selected icon to download the file:



No: 0326



No: 4420/2021
Valid until:
05.09.2026



No: 88-128652



No:
B_BK_60112_0425_2024
Valid until:
24.01.2030



No: 0326



No: 2291559.02-
UAE
Valid until:
05.11.2026



REACH
compliant



RoHS
compliant

No: 0326




No: V1



No: V1.19



Producer	TM TECHNOLOGIE
Category	emergency luminaires
Application	evacuation route direction
Family	ONTEC G
Colour/Colour - RAL	black , RAL9005
Colour structure	matte , satin, smooth
Version	autotest
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	125x125 mm
Evacuation sign dimensions	250x125 mm
Pictogram type	foil
Graphic number	K6
Pictogram logo	TM TECHNOLOGIE
Luminous flux	>350 cd/m²
Visibility	25 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
Light source	LED
Maximum light power	0.9 W
LED lifetime	50000 h
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	251 mm x 29 mm x 198 mm



* Some of mounting methods are possible only with additonal accessory dedicated for that product.