

ONTEC S M2 102 M AT W COLD TM-OS.M2ATM16CW

Click on the selected icon to download the file:



No: 1026



No: 4662/2022
Valid until:
02.06.2027



No: 88-139797



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030




No: 1026



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 1026



No: V1





No: V3.0



Producer	TM TECHNOLOGIE
Application	anti-panic lighting
Family	ONTEC S
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	M
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	241 lm
Light source	LED
Maximum light power	4.7 W
Active power	6.5 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	-15 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C 6.4V 1.5Ah

Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.