

WLD+40038_DALI_DT8

SYSTEM SHIFT DALI TW8 - LINE M FIXTURE LINE 602X23X42MM 17W 100ST WHITE DALI TW8 5YW.



Power	6 W	Voltage	48 V
Colour temperature	3000 / 4000 / 6000 K	Colour of light	CCT
Beam angle	24 °	Degree of protection (IP)	IP20

Technical data

Logistics data

Code	WLD+40038_DALI_DT8
Power	6 W
Nominal current	115 mA
Voltage	48 V
Energy consumption	6 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	BOKE
Power factor	1
Useful luminous flux*	500 lm (360°)
Luminous flux	350 lm (360°)
Lamp efficacy	83 lm/W
Luminous intensity	1050 cd
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	24 °
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	35x140x178 mm
For use	Inside
Assembly method	on track 48V
Made in	PRC
Other	DT8 ,

*applies to the LED source used

Related documents

 Declaration of
Conformity