

PRODUCT CARD

**Manufacturer: PowerWalker
ZI3528**

UPS POWERWALKER VI 1200 SH FR LINE-INTERACTIVE 1200VA 2X FRENCH OUTLETS + 2X IEC C13 USB-B

Catalog number: VI 1200 SH FR



Product description

PowerWalker VI 1200 SH FR is a Line- Interactive UPS which provides high performance and reliable and cost-effective backup power protection. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection, and green power function for energy saving. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or SMB (small medium business) application.

- 1200VA Line-Interactive UPS
- 2x French Outlet, 2x IEC C13, RJ-11/RJ-45 (in/out)
- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ-11/RJ-45 surge protection
- Monitoring software included
- Green function for energy saving
- LED Display show UPS status

Product features

Length [mm]	364,00
Width [mm]	139,00
Height [mm]	195,00

Supported Operating Systems	FreeBSD; Linux; MAC; Windows XP; Windows 7; Windows 8; Windows 10; Windows 11
Connectors	RJ-45; RJ-11; USB Type-B
Power [W]	600,00
Apparent power [VA]	1 200,00
Input voltage [V]	230,00
Input voltage range [V]	from 170,00 up to 280,00
Input frequency range [Hz]	from 50,00 up to 60,00
Output voltage [V]	230,00
Output voltage regulation [%]	+/- 10
Input frequency regulation [Hz]	+/- 1
Waveform type	Modified sine wave
Battery quantity	2,00
Recharge time [h]	4,00
Expansion slot	No
Colour	Black
Environment temperature [°C]	from 0,00 up to 40,00
Environment humidity [%]	from 0,00 up to 90,00
Max transfer time [ms]	8,00
Software	WinPower
Output frequency [Hz]	50,00
Battery capacity [Ah]	7,00
Battery weight [kg]	4,12
Battery runtime at 50% load [min]	11,00
Battery runtime at 100% load [min]	1,30
AC/DC Transfer time [ms]	from 4,00 up to 8,00
Protections	Surge protection
Functions	Automatic voltage regulation (AVR)
Type of casing	Desktop
Output acceptable voltage range [V]	from 230,00 up to 230,00
Device efficiency [%]	95,00
UPS topology	Line-interactive (VI)
PowerFactor	0,50
Weight [kg]	8,60
Outlet type	IEC C13; Type E
Number of outlets	4,00
Work signal	LED
Battery pack connector	No
Battery string voltage [V]	24,00
Included Accessories	User guide; USB cable
Weatherproof rating	IP20
Cold start	Yes
Battery type	Lead acid VRLA AGM
Audible alarms	Yes
Automatic Voltage Regulation (AVR)	Single boost; Single buck
Required battery voltage	2x 12V

Logistics data

ean	4260074975116
Unit width [cm]	29,00
Unit height [cm]	23,00
Unit length [cm]	45,00

Unit weight [kg]	45,00
VAT rate [%]	23,00
Warranty	24 (external)
Duty code	85044095
Country of origin	CN