

# **PRODUCT CARD**

**Manufacturer: PowerWalker  
ZI3529**

## **UPS POWERWALKER VI 2200 SH FR LINE-INTERACTIVE 2200VA 2X FRENCH + 2X IEC C13 USB-B**

**Catalog number: VI 2200 SH FR**



### **Product description**

PowerWalker VI 2200 SH FR is a Line- Interactive UPS which provides high performance and reliable and cost-effective backup power protection. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection, and green power function for energy saving. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or SMB (small medium business) application.

- 2200VA Line-Interactive UPS
- 2x French Outlet, 2x IEC C13, RJ-11/RJ-45 (in/out)
- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ-11/RJ-45 surge protection
- Monitoring software included
- Green function for energy saving
- LED Display show UPS status

### **Product features**

|             |        |
|-------------|--------|
| Length [mm] | 364,00 |
| Width [mm]  | 139,00 |
| Height [mm] | 195,00 |

|                                     |                                                                               |
|-------------------------------------|-------------------------------------------------------------------------------|
| Supported Operating Systems         | FreeBSD; Linux; MAC; Windows XP; Windows 7; Windows 8; Windows 10; Windows 11 |
| Connectors                          | RJ-45; RJ-11; USB Type-B                                                      |
| Power [W]                           | 1 200,00                                                                      |
| Apparent power [VA]                 | 2 200,00                                                                      |
| Input voltage [V]                   | 230,00                                                                        |
| Input voltage range [V]             | from 170,00 up to 280,00                                                      |
| Input frequency range [Hz]          | from 50,00 up to 60,00                                                        |
| Output voltage [V]                  | 230,00                                                                        |
| Output voltage regulation [%]       | +/- 10                                                                        |
| Input frequency regulation [Hz]     | +/- 1                                                                         |
| Waveform type                       | Modified sine wave                                                            |
| Battery quantity                    | 2,00                                                                          |
| Recharge time [h]                   | 4,00                                                                          |
| Expansion slot                      | No                                                                            |
| Colour                              | Black                                                                         |
| Environment temperature [°C]        | from 0,00 up to 40,00                                                         |
| Environment humidity [%]            | from 0,00 up to 90,00                                                         |
| Max transfer time [ms]              | 8,00                                                                          |
| Software                            | WinPower                                                                      |
| Output frequency [Hz]               | 50,00                                                                         |
| Battery capacity [Ah]               | 9,00                                                                          |
| Battery weight [kg]                 | 4,60                                                                          |
| Battery runtime at 50% load [min]   | 5,00                                                                          |
| Battery runtime at 100% load [min]  | 0,50                                                                          |
| AC/DC Transfer time [ms]            | from 4,00 up to 8,00                                                          |
| Protections                         | Surge protection                                                              |
| Noise level [dB]                    | 45,00                                                                         |
| Functions                           | Automatic voltage regulation (AVR)                                            |
| Type of casing                      | Desktop                                                                       |
| Output acceptable voltage range [V] | from 170,00 up to 280,00                                                      |
| Device efficiency [%]               | 95,00                                                                         |
| UPS topology                        | Line-interactive (VI)                                                         |
| PowerFactor                         | 0,55                                                                          |
| Weight [kg]                         | 10,20                                                                         |
| Outlet type                         | IEC C13; Type E                                                               |
| Number of outlets                   | 4,00                                                                          |
| Work signal                         | LED                                                                           |
| Battery pack connector              | No                                                                            |
| Battery string voltage [V]          | 24,00                                                                         |
| Included Accessories                | User guide; USB cable                                                         |
| Weatherproof rating                 | IP20                                                                          |
| Cold start                          | Yes                                                                           |
| Battery type                        | Lead acid VRLA AGM                                                            |
| Audible alarms                      | Yes                                                                           |
| Automatic Voltage Regulation (AVR)  | Single boost; Single buck                                                     |
| Required battery voltage            | 2x 12V                                                                        |

## **Logistics data**

|                  |               |
|------------------|---------------|
| ean              | 4260074975123 |
| Unit width [cm]  | 29,00         |
| Unit height [cm] | 23,00         |

|                   |               |
|-------------------|---------------|
| Unit length [cm]  | 45,00         |
| Unit weight [kg]  | 45,00         |
| VAT rate [%]      | 23,00         |
| Warranty          | 24 (external) |
| Duty code         | 85044095      |
| Country of origin | CN            |