

PRODUCT CARD

Manufacturer: PowerWalker
ZI3526

UPS POWERWALKER VI 650 SH FR LINE-INTERACTIVE 650VA 2X FRENCH OUTLETS USB-B

Catalog number: VI 650 SH FR



Product description

PowerWalker VI 650 SH FR provides comprehensive protection and high power density in small and economic package. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ-11 surge protection. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or small office application.

- 650VA Line-Interactive UPS
- 2x French Outlet, RJ-11 (in/out)
- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ-11 surge protection
- Monitoring software included
- Green function for energy saving

Product features

Power [W]	360,00
Apparent power [VA]	650,00
Input voltage [V]	230,00
Output voltage [V]	230,00
Length [mm]	290,00
Width [mm]	100,00

Height [mm]	143,00
Supported Operating Systems	FreeBSD; Linux; MAC; Windows XP; Windows 7; Windows 8; Windows 10; Windows 11
Connectors	RJ-11; USB Type-B
Output frequency [Hz]	50,00
Input frequency regulation [Hz]	+/- 1
Waveform type	Modified sine wave
Battery quantity	1,00
Recharge time [h]	4,00
Expansion slot	No
Colour	Black
Environment temperature [°C]	from 0,00 up to 40,00
Environment humidity [%]	from 0,00 up to 90,00
Max transfer time [ms]	8,00
Battery capacity [Ah]	7,00
Software	WinPower
Input voltage range [V]	from 170,00 up to 280,00
Input frequency range [Hz]	from 50,00 up to 60,00
Output voltage regulation [%]	+/- 10
Battery weight [kg]	2,06
Battery runtime at 50% load [min]	6,00
Battery runtime at 100% load [min]	0,10
AC/DC Transfer time [ms]	from 4,00 up to 8,00
Protections	Surge protection
Functions	Automatic voltage regulation (AVR)
Type of casing	Desktop
Output acceptable voltage range [V]	from 230,00 up to 230,00
Device efficiency [%]	95,00
UPS topology	Line-interactive (VI)
PowerFactor	0,55
Weight [kg]	4,40
Outlet type	Type E
Number of outlets	2,00
Work signal	LED
Battery pack connector	No
Battery string voltage [V]	12,00
Included Accessories	User guide; USB cable
Weatherproof rating	IP20
Cold start	Yes
Battery type	Lead acid VRLA AGM
Audible alarms	Yes
Automatic Voltage Regulation (AVR)	Single boost; Single buck
Required battery voltage	1x 12V

Logistics data

ean	4260074975093
Unit width [cm]	22,00
Unit height [cm]	14,00
Unit length [cm]	33,00
Unit weight [kg]	33,00
Quantity in a carton [units]	4.000
Carton width [cm]	34,50
Carton height [cm]	24,50

Carton length [cm]	58,50
Carton weight [kg]	58,50
VAT rate [%]	23,00
Warranty	24 (external)
Duty code	85044095
Country of origin	CN