

PRODUCT CARD

**Manufacturer: PowerWalker
ZI4716**

**UPS POWERWALKER VI 2000 LCD LINE-INTERACTIVE 2000VA 2X SCHUKO OUTLETS + 2X IEC
C13 USB-B LCD**

Catalog number: VI 2000 LCD



Product description

PowerWalker VI 2000 LCD provides comprehensive protection and high power density in small and economic package. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ-11/RJ-45 surge protection, and green power function for energy saving. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or small office application.

- 2000VA Line-Interactive UPS
- LCD Display for status view
- 2x Schuko Outlet, 2x IEC C13, RJ-11/RJ-45 (in/out)
- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ-11/RJ-45 surge protection
- Monitoring software included
- Green function for energy saving (can be enabled by Software)

Product features

Length [mm]	397,00
Width [mm]	146,00
Height [mm]	205,00

Supported Operating Systems	FreeBSD; Linux; MAC; Windows XP; Windows 7; Windows 8; Windows 10; Windows 11
Connectors	RJ-45; RJ-11; USB Type-B
Power [W]	1 200,00
Apparent power [VA]	2 000,00
Input voltage [V]	230,00
Input voltage range [V]	from 162,00 up to 290,00
Input frequency range [Hz]	from 50,00 up to 60,00
Output voltage [V]	230,00
Output voltage regulation [%]	+/- 10
Output frequency [Hz]	50,00
Input frequency regulation [Hz]	+/- 1
Waveform type	Modified sine wave
Battery quantity	2,00
Recharge time [h]	4,00
Expansion slot	No
Colour	Black
Noise level [dB]	40,00
Environment temperature [°C]	from 0,00 up to 40,00
Environment humidity [%]	from 0,00 up to 90,00
Max transfer time [ms]	6,00
Software	View Power
Battery weight [kg]	4,60
Battery runtime at 50% load [min]	5,00
Battery runtime at 100% load [min]	0,70
AC/DC Transfer time [ms]	from 2,00 up to 6,00
Protections	Surge protection
Battery capacity [Ah]	9,00
Functions	Automatic voltage regulation (AVR)
Type of casing	Desktop
Output acceptable voltage range [V]	from 230,00 up to 230,00
Device efficiency [%]	95,20
UPS topology	Line-interactive (VI)
PowerFactor	0,60
Weight [kg]	12,10
Outlet type	IEC C13; Type F
Number of outlets	4,00
Work signal	LCD
Battery pack connector	No
Battery string voltage [V]	24,00
Included Accessories	User guide; USB cable; IEC cable; Power cord
Weatherproof rating	IP20
Battery type	Lead acid VRLA AGM
Audible alarms	Yes
Required battery voltage	2x 12V

Logistics data

ean	4260074972795
Unit width [cm]	28,50
Unit height [cm]	23,00
Unit length [cm]	49,00
Unit weight [kg]	49,00

VAT rate [%]	23,00
Warranty	24 (external)
Duty code	85044095
Country of origin	CN