MUNDIAL

INDUSTRIAL PLUGS AND SOCKETS

Description: IP66-IP67 SLOPING FLUSH-FIT SOCKET 2P+E 220V 16A 6H

Reference:
02801

Characteristics:

Product type:	Low voltage sloping flush-fit socket
Current:	16A
Poles:	2P+E
Voltage:	200…250V
Frecuency(Hz):	50/60Hz
Time code:	6h
Colour:	Blue
Weight (kg):	0,15
Dimensions:	(AxB/CxD) 80x97 / 60x73 mm
Materials:	Halogen-free plastic materials. Plastic parts: polyamide 6. Contacts: copper-zinc alloy
Packaging units:	8

Technical data:

Degree of protection:	IP66-IP67
Degree of protection remarks:	
Resistance to impact:	IK08
Glow wire resistance:	960 ºC
Ball pressure test:	125 ºC
Ambient temperature range:	-25 ºC / +40 ºC

Certifications and norms:

Directive:	2014/35/EU
Standards:	IEC 60309-1-2
Certificates:	CE

Codes:


EAN:	8431044028019
Customs tariff number:	85.36.69.90
ETIM 8.0:	EC001317


MUNDIAL

INDUSTRIAL PLUGS AND SOCKETS

Description: IP66-IP67 SLOPING FLUSH-FIT SOCKET 2P+E 220V 16A 6H

Reference: 02801







Detailed drawing:

- https://www.ide.es/docs/planos/pdf/02801.pdf
- https://www.ide.es/docs/planos/dxf/02801.dxf
- https://www.ide.es/docs/planos/stp/02801.stp

Dimensions:

Current	Poles	Dimensions								
		A	B	C	D	E	F	G	H	Ø Oblong (H x W)
16A	2P+E	80	97	60	73	38	50	51	17	53
	3P+E	80	97	60	73	38	52	56	14	60
	3P+N+E	80	97	60	73	38	55	65	15	66
32A	2P+E	80	97	60	73	48	59	65	14	68
	3P+E	80	97	60	73	48	59	65	14	68
	3P+N+E	80	97	60	73	48	61	70	11	74
63A	2P+E	100	112	80	88	64	80	109	-	92x82
	3P+E	100	112	80	88	64	80	109	-	92x82
	3P+N+E	100	112	80	88	64	80	109	-	92x82
125A	2P+E	120	130	100	108	92	77	124	-	102x90
	3P+E	120	130	100	108	92	77	124	-	102x90
	3P+N+E	120	130	100	108	92	77	124	-	102x90

Sustainability:

RoHS - REACH

Product end of life stage:

Product concerned in the WEEE regulations.

Supply:

Supplied in a single box per packaging multiple