ABS BASIC SERIES

ABS WALL-MOUNTING CABINETS

Description: ABS WALL-MOUNTING CABINET 350x250x150 OPAQUE DOOR

Reference:
ABS352515

Characteristics:

Product type:	Wall-mounting cabinet
Dimensions cabinet:	(AxBxC) 350x250x150 mm
Installation:	Surface
Type of door:	Opaque door
Locking:	Triangle lock
Finish:	
Colour:	RAL 7035
Mounting plate:	Mounting plate: 1-mm galvanized steel
Weight (kg):	2.2
Materials:	HB ABS. Double insulation: Clase II
Thickness:	
Sealing gasket:	
Door material:	
Capacity:	
Max. cabinet load:	
Max. mounting plate load:	5 kg
Max. door load:	

Technical data:

Degree of protection:	IP65
NEMA degree of protection:	
Resistance to impact:	IK08
Ambient temperature range:	-25 ºC / +60 ºC
Maximum material temperature:	80 ºC
Maximum operating voltage:	690 V AC

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208
Certificates:	

CE

Codes:

EAN:	8431044370187
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000261

ABS BASIC SERIES

ABS WALL-MOUNTING CABINETS

Description: ABS WALL-MOUNTING CABINET 350x250x150 OPAQUE DOOR

Reference: ABS352515



Standard drawing

Detailed drawing:
https://www.ide.es/downloads/planos/pdf/ABS352515.pdf
https://www.ide.es/downloads/planos/dxf/ABS352515.dxf
https://www.ide.es/downloads/planos/stp/ABS352515.stp

Cable entry:		**Body to be flush-fitted:**	-
Wall fixing:	(FxG) 230x175 mm	**Wall fixing material:**	
Inside usable space:	(DxE) 307x200 mm	**Glass door with transparent panel:**	
No. Hinges:		**Door profiles:**	

Sustainability:

RoHS

Product end of life:

It does not require specific recycling operations.

Supply:

Supplied in individual cardboard packaging. Includes the wall bracket (Ref. 29584) and the triangular key (Ref. 29583)

Recommended applications:

Specially designed for applications in the industrial automation and control sector.