ARGENTA PLUS SERIES

IP65-IP55 STEEL FLOOR-STANDING COMPACT CABINETS (BIG)

Description: IP55 COMPACT FLOOR-STANDING CABINET (BIG) 2000x1600x400 DOUBLE OPAQUE DOOR WITH MOUNTING PLATE

Reference:
BIG20016040POD

Characteristics:

Product type:	Steel floor-standing compact cabinet (BIG)
Dimensions cabinet:	(AxBxC) 2000x1600x400 mm
Installation:	Surface
Type of door:	Double opaque door
Locking:	4-point quarter-turn lock, 5 mm double-bit insert, color RAL 5013 Cobalt Blue
Finish:	Coated with primer, and hardened polyester paint, textured, with UV protection
Colour:	RAL 7035
Mounting plate:	With flat mounting plate. 3-mm galvanised sheet steel
Weight (kg):	260,9
Materials:	Cold-rolled steel EN 10130+A1
Thickness:	Enclosure: 1,5 mm. Door: 2 mm. Cable entry lid: 1,2 mm
Sealing gasket:	Injected polyurethane sealing gasket
Door material:	
Capacity:	
Max. cabinet load:	
Max. mounting plate load:	
Max. door load:	

Technical data:

Degree of protection:	IP55
NEMA degree of protection:	NEMA 1, 12
Resistance to impact:	IK10
Ambient temperature range:	-25 ºC / +60 ºC
Maximum material temperature:	
Maximum operating voltage:	1000 V AC / 1500 V DC

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208, IEC 61439-1
Certificates:	

Codes:


EAN:	8431044262543
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000261

ARGENTA PLUS SERIES

IP65-IP55 STEEL FLOOR-STANDING COMPACT CABINETS (BIG)

Description: IP55 COMPACT FLOOR-STANDING CABINET (BIG) 2000x1600x400 DOUBLE OPAQUE DOOR WITH MOUNTING PLATE

Reference: BIG20016040POD





Standard drawing

Detailed drawing: https://www.ide.es/downloads/planos/pdf/BIG20016040POD.pdf

https://www.ide.es/downloads/planos/dxf/BIG20016040POD.dxf

https://www.ide.es/downloads/planos/stp/BIG20016040POD.stp

Cable entry:	(Width x Depth) 2x (570x270) mm	**Body to be flush-fitted:**	-
Wall fixing:	-	**Wall fixing material:**	
Inside usable space:	(HeightxWidthxDepth) 1910x1510x357 mm	**Glass door with transparent panel:**	-
No. Hinges:		**Door profiles:**	

Sustainability:

RoHS - REACH

Product end of life:

It does not require specific recycling operations.

Supply:

Supplied on a pallet, protected with front and rear cardboard sheets, corner protectors and film. The plate is supplied assembled. Cable-gland lid included. Removable rear panel included.

Recommended applications:

Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.