# ECO-STAR

## ECO-STAR SYSTEM

Description: IP65 SURFACE BOX 2x18 (36) MOD. CDN36PT2F+CSNPLUS

Reference:
**CDN36PT2F/PLUS**

## Characteristics:

| | |
|---|---|
| **Product type:** | Join of distribution boxes and boxes for industrial sockets |
| **Exterior dimensions (Height x Width x Depth):** | 436x560x147 mm |
| **Dimensions of the flush-fit gap (HxWxD):** | - |
| **Number of modules:** | 3x12 (36) DIN rail + additional |
| **Installation:** | Surface |
| **Color:** | RAL 7035 |
| **Window:** | Transparent |
| **Weight (kg):** | 4,19 |
| **Cable entry:** | |
| **Components:** | - |
| **Materials:** | Halogen-free plastic materials. Frame and base: ABS. UV protection under ISO standard 4892-2, Method A: 500h |
| **Lid-window-door material:** | Tinted PC, UV protection |

## Technical data:

| | |
|---|---|
| **Degree of protection:** | IP65 |
| **Resistance to impact:** | IK08 |
| **Glow wire resistance:** | 650 ºC |
| **Ball pressure test:** | 70 ºC |
| **Ambient temperature range:** | -25 ºC / +60 ºC |
| **Maximum material temperature:** | |
| **Maximum operating voltage:** | 1000 V AC / 1500 V DC |
| **Rated current:** | |
| **Double insulation:** | Class II |

## Certificates and standards:

| | |
|---|---|
| **Directive:** | 2014/35/EU |
| **Standards:** | IEC 62208 |
| **Certificates:** | |

## Codes:

| | |
|---|---|
| **EAN:** | 8431044122465 |
| **Customs tariff number:** | 85.38.10.00 |
| **ETIM 8.0:** | EC000379 |

# ECO-STAR

## ECO-STAR SYSTEM

Description: IP65 SURFACE BOX 2x18 (36) MOD. CDN36PT2F+CSNPLUS

**Reference:** CDN36PT2F/PLUS



**Exterior dimensions (Height x Width x Depth):**

436x560x147 mm

**Dimensions of the flush-fit gap (Height x Width x Depth):**

-

## Sustainability:

RoHS - REACH

## Product end of life:

It does not require specific recycling operations.

## Supply:

Supplied in individual cardboard packaging. When several items are sent together, they are bundled together with transparent film.

**Packaging units:** 1

## Recommended applications:

Industrial and outdoor environments. Industrial sites, docks, swimming pools, garages, anywhere that requires a high degree of protection against dust, splashes and impacts.