ECO-STAR

ECO-STAR SYSTEM

Description: IP65 SURFACE BOX 1x18 MOD. CSN18PT+CSNPLUS

Reference:
CSN18PT/PLUS

Characteristics:

Product type:	Join of distribution boxes and boxes for industrial sockets
Exterior dimensions (Height x Width x Depth):	436x560x147 mm
Dimensions of the flush-fit gap (HxWxD):	-
Number of modules:	1x18 DIN rail + additional
Installation:	Surface
Color:	RAL 7035
Window:	Transparent
Weight (kg):	3,55
Cable entry:	
Components:	-
Materials:	Halogen-free plastic materials. Frame and base: ABS. Recommended for outdoor use: UV protection under ISO standard 4892-2, Method A: 500h.
Lid-window-door material:	Tinted PC, UV protection

Technical data:

Degree of protection:	IP65
Resistance to impact:	IK08
Glow wire resistance:	650 ºC
Ball pressure test:	70 ºC
Ambient temperature range:	-25 ºC / +60 ºC
Maximum material temperature:	
Maximum operating voltage:	1000 V AC / 1500 V DC
Rated current:	
Double insulation:	Class II

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 61439-1
Certificates:	

Codes:

EAN:	8431044122403
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000379

ECO-STAR

ECO-STAR SYSTEM

Description: IP65 SURFACE BOX 1x18 MOD. CSN18PT+CSNPLUS

Reference: CSN18PT/PLUS



Exterior dimensions (Height x Width x Depth):

436x560x147 mm

Dimensions of the flush-fit gap (Height x Width x Depth):

-

Sustainability:

RoHS - REACH

Product end of life:

It does not require specific recycling operations.

Supply:

Supplied in individual cardboard packaging. When several items are sent together, they are bundled together with transparent film.

Packaging units: 1

Recommended applications:

Industrial and outdoor environments. Industrial sites, docks, swimming pools, garages, anywhere that requires a high degree of protection against dust, splashes and impacts.