LIGHT

IP65-67 JUNCTION BOXES

Description: IP65-67 WATERTIGHT JUNCTION BOX WITH PLAIN SIDES AND TRANSPARENT COVER

Reference:
ELT171

Characteristics:

Product type:	Watertight junction boxes with transparent cover and plain sides
Exterior dimensions (Height x Width x Depth):	155x179x100 mm
Dimensions of the flush-fit gap (HxWxD):	-
Number of modules:	-
Installation:	Surface
Color:	RAL 7035
Window:	Transparent
Weight (kg):	0,37
Cable entry:	-
Components:	-
Materials:	Matériaux plastiques sans halogène. Base: PS antichoc
Lid-window-door material:	Tinted PC, UV protection

Technical data:

Degree of protection:	IP65 and IP67
Resistance to impact:	IK07
Glow wire resistance:	650 ºC
Ball pressure test:	70 ºC
Ambient temperature range:	-25 ºC / +40 ºC
Maximum material temperature:	
Maximum operating voltage:	1000 V AC / 1500 V DC
Rated current:	
Double insulation:	Class II

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 60670-22
Certificates:	

CE

Codes:

EAN:	8431044191201
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC002600

LIGHT

IP65-67 JUNCTION BOXES

Description: IP65-67 WATERTIGHT JUNCTION BOX WITH PLAIN SIDES AND TRANSPARENT COVER

Reference: ELT171







Detailed drawing:

- https://www.ide.es/downloads/planos/pdf/ELT171.pdf
- https://www.ide.es/downloads/planos/dxf/ELT171.dxf
- https://www.ide.es/downloads/planos/stp/ELT171.stp

Exterior dimensions (Height x Width x Depth):

155x179x100 mm

Dimensions of the flush-fit gap (Height x Width x Depth):

-

Sustainability:

RoHS - REACH

Supply:

The boxes are supplied individually, shrink-wrapped and in multiple cardboard packaging, according to minimum packaging units.

Packaging units: 10

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial and outdoor environments. Industrial sites, docks, swimming pools, garages, anywhere that requires a high degree of protection against dust, splashes and impacts.