LIGHT

IP65 JUNCTION BOXES

Description: IP65 WATERTIGHT JUNCTION BOX WITH CONICAL CABLE GLANDS AND TRANSPARENT LID

Reference:
EVT322

Characteristics:

Product type:	Watertight junction boxes with transparent cover and conical cable glands
Exterior dimensions (Height x Width x Depth):	253x342x132 mm
Dimensions of the flush-fit gap (HxWxD):	-
Number of modules:	-
Installation:	Surface
Color:	RAL 7035
Window:	Transparent
Weight (kg):	0,98
Cable entry:	12xM40
Components:	-
Materials:	Matériaux plastiques sans halogène. Base: PS antichoc
Lid-window-door material:	Tinted PC, UV protection

Technical data:

Degree of protection:	IP65
Resistance to impact:	IK07
Glow wire resistance:	650 ºC
Ball pressure test:	70 ºC
Ambient temperature range:	-25 ºC / +40 ºC
Maximum material temperature:	
Maximum operating voltage:	1000 V AC / 1500 V DC
Rated current:	
Double insulation:	Class II

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 60670-22
Certificates:	

CE

Codes:

EAN:	8431044195209
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC002600

LIGHT

IP65 JUNCTION BOXES

Description: IP65 WATERTIGHT JUNCTION BOX WITH CONICAL CABLE GLANDS AND TRANSPARENT LID

Reference: EVT322



Detailed drawing:

https://www.ide.es/downloads/planos/pdf/EVT322.pdf

https://www.ide.es/downloads/planos/dxf/EVT322.dxf

https://www.ide.es/downloads/planos/stp/EVT322.stp

Exterior dimensions (Height x Width x Depth):

253x342x132 mm

Dimensions of the flush-fit gap (Height x Width x Depth):

-

Sustainability:

RoHS - REACH

Supply:

The boxes are supplied individually, shrink-wrapped and in multiple cardboard packaging, according to minimum packaging units. Boxes with conical cable glands are supplied with the cone assembled.

Packaging units: 6

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial and outdoor environments. Industrial sites, docks, swimming pools, garages, anywhere that requires a high degree of protection against dust, splashes and impacts.