# ARGENTA INOX SERIES

## IP66 STAINLESS STEEL WALL-MOUNTING CABINETS

Description: IP66 304L-INOX WALL-MOUNTING CABINET 500x400x200

Reference:
**INX504020**

## Characteristics:

| | |
|---|---|
| **Product type:** | 304L Stainless steel wall-mounting cabinet |
| **Dimensions cabinet:** | (AxBxC) 500x400x200 mm |
| **Installation:** | Surface |
| **Type of door:** | Single opaque door. Reversible |
| **Locking:** | 5-mm double-bit painted zamak lock - Two 1-point lock |
| **Finish:** | Scotch 320 satin finish |
| **Colour:** | - |
| **Mounting plate:** | With flat mounting plate. 2-mm galvanised sheet steel |
| **Weight (kg):** | 11,6 |
| **Materials:** | AISI 304L stainless steel |
| **Thickness:** | Enclosure: 1.2 mm. Door: 1.2 mm. |
| **Sealing gasket:** | Injected polyurethane sealing gasket |
| **Door material:** | |
| **Capacity:** | |
| **Max. cabinet load:** | 225 kg |
| **Max. mounting plate load:** | 200 kg |
| **Max. door load:** | 25 kg |

## Technical data:

| | |
|---|---|
| **Degree of protection:** | IP66 |
| **NEMA degree of protection:** | NEMA 1, 4, 4x, 12 |
| **Resistance to impact:** | IK10 |
| **Ambient temperature range:** | -25 ºC / +60 ºC |
| **Maximum material temperature:** | |
| **Maximum operating voltage:** | 1000V AC / 1500V DC |

## Certificates and standards:

| | |
|---|---|
| **Directive:** | 2014/35/EU |
| **Standards:** | IEC 62208, IEC 61439-1 |
| **Certificates:** | UL508A |

## Codes:


| | |
|---|---|
| **EAN:** | 8431044088624 |
| **Customs tariff number:** | 85.38.10.00 |
| **ETIM 8.0:** | EC000261 |

# ARGENTA INOX SERIES

## IP66 STAINLESS STEEL WALL-MOUNTING CABINETS

Description: IP66 304L-INOX WALL-MOUNTING CABINET 500x400x200

**Reference:** INX504020






Standard drawing

**Detailed drawing:** https://www.ide.es/downloads/planos/pdf/INX504020.pdf

https://www.ide.es/downloads/planos/dxf/INX504020.dxf

https://www.ide.es/downloads/planos/stp/INX504020.stp

| | | | |
|---|---|---|---|
| **Cable entry:** | - | **Body to be flush-fitted:** | - |
| **Wall fixing:** | (HeightxWidth) 460x360 mm | **Wall fixing material:** | |
| **Inside usable space:** | (HeightxWidthxDepth) 450x350x179 mm | **Glass door with transparent panel:** | - |
| **No. Hinges:** | 2 | **Door profiles:** | 2 |

## Sustainability:

RoHS - REACH

## Product end of life:

It does not require specific recycling operations.

## Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag. The cabinet is protected by a plastic bag. Mounting plate is supplied unassembled inside the packaging.

## Recommended applications:

Industrial environments and outdoor facilities with aggressive agents or saline environments. Food, chemical and petrochemical industries, where a high degree of hygiene is required.