ARGENTA INOX SERIES

IP66 STAINLESS STEEL WALL-MOUNTING CABINETS

Description: IP66 304L-INOX WALL-MOUNTING CABINET 800x600x300 - TRANSP.DOOR

Reference:
INXT806030

Characteristics:

Product type:	304L Stainless steel wall-mounting cabinet
Dimensions cabinet:	(AxBxC) 800x600x300 mm
Installation:	Surface
Type of door:	Single transparent door. Revrsible
Locking:	5-mm double-bit painted zamak lock - One 3-point lock
Finish:	Scotch 320 satin finish
Colour:	-
Mounting plate:	With flat mounting plate. 2-mm galvanised sheet steel
Weight (kg):	29,8
Materials:	AISI 304L stainless steel
Thickness:	Enclosure: 1.5 mm. Door: 1.5 mm.
Sealing gasket:	Injected polyurethane sealing gasket
Door material:	4-mm thick tempered transparent glass
Capacity:	-
Max. cabinet load:	325 kg
Max. mounting plate load:	300 kg
Max. door load:	25 kg

Technical data:

Degree of protection:	IP66
NEMA degree of protection:	NEMA 1, 4, 4x, 12
Resistance to impact:	IK09
Ambient temperature range:	-25 ºC / +60 ºC
Maximum material temperature:	
Maximum operating voltage:	1000 V AC / 1500 V DC

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208, IEC 61439-1
Certificates:	UL508A

Codes:

EAN:	8431044227375
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000261

ARGENTA INOX SERIES

IP66 STAINLESS STEEL WALL-MOUNTING CABINETS

Description: IP66 304L-INOX WALL-MOUNTING CABINET 800x600x300 - TRANSP.DOOR

Reference: INXT806030



Standard drawing

Detailed drawing: https://www.ide.es/downloads/planos/pdf/INXT806030.pdf

https://www.ide.es/downloads/planos/stp/INXT806030.stp

Cable entry:	-	**Body to be flush-fitted:**	-
Wall fixing:	(HeightxWidth) 760x560 mm	**Wall fixing material:**	
Inside usable space:	(HeightxWidthxDepth) 750x550x279 mm	**Glass door with transparent panel:**	(HeightxWidth) 697x449 mm
No. Hinges:	2	**Door profiles:**	2

Sustainability:

RoHS - REACH

Product end of life:

It does not require specific recycling operations.

Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag. The cabinet is protected by a plastic bag. Mounting plate is supplied assembled inside the cabinet.

Recommended applications:

Industrial environments and outdoor facilities with aggressive agents or saline environments. food, chemical and petrochemical industries, where a high degree of hygiene is required.