GLASS SERIES

IP66 POLYESTER WALL-MOUNTING CABINETS

Description: IP66 POLYESTER WALL-MOUNTING CABINET 800x1000x300 OPAQUE DOOR

Reference:
POL8010030

Characteristics:

Product type:	Polyester wall-mounting cabinet
Dimensions cabinet:	(AxBxC) 800x1000x300 mm
Installation:	Surface
Type of door:	Single opaque door
Locking:	3-mm double-bit lock (1P)
Finish:	
Colour:	RAL 7035
Mounting plate:	
Weight (kg):	17,2
Materials:	Fibreglass-reinforced polyester
Thickness:	Enclosure: 3 mm. Door: 3 mm.
Sealing gasket:	Injected polyurethane sealing gasket
Door material:	Fibreglass-reinforced polyester
Capacity:	
Max. cabinet load:	96 kg
Max. mounting plate load:	96 kg
Max. door load:	14 kg

Technical data:

Degree of protection:	IP66
NEMA degree of protection:	
Resistance to impact:	IK10
Ambient temperature range:	-30 ºC / +60 ºC
Maximum material temperature:	
Maximum operating voltage:	1000 V AC / 1500 V DC

Certificates and standards:

Directive:	2014/35/EU
Standards:	IEC 62208, IEC 61439-1
Certificates:	

CE

Codes:


EAN:	8431044516509
Customs tariff number:	85.38.10.00
ETIM 8.0:	EC000261

GLASS SERIES

IP66 POLYESTER WALL-MOUNTING CABINETS

Description: IP66 POLYESTER WALL-MOUNTING CABINET 800x1000x300 OPAQUE DOOR

Reference: POL8010030





Standard drawing

Detailed drawing: https://www.ide.es/downloads/planos/pdf/POL8010030.pdf

https://www.ide.es/downloads/planos/dxf/POL8010030.dxf

https://www.ide.es/downloads/planos/stp/POL8010030.stp

Cable entry:	-	**Body to be flush-fitted:**	-
Wall fixing:	(HeightxWidth) 709x918 mm	**Wall fixing material:**	
Inside usable space:	(HeightxWidth) 729x956 mm	**Glass door with transparent panel:**	-
No. Hinges:	4	**Door profiles:**	

Sustainability:

RoHS - REACH

Product end of life:

It does not require specific recycling operations.

Supply:

Supplied in individual packaging. The accessories for fitting the mounting plate are fitted on the cabinet. Plate supplied in individual packaging if requested as an accessory.

Recommended applications:

Industrial environments and outdoor facilities. food, chemical and pharmaceutical industries, transformer sub-stations and outdoor areas where durability and resistance against chemicals and UV rays are necessary. Suitable for use in marine environments.