UPS ARMAC

OFFICE ON-LINE PF1 2000VA DUST FREE









PRODUCT SPECIFICATION:

UPS topology	On-line (VFI)
Power	2 000 W
PowerFactor	1
Device efficiency	95,5 %
Type of casing	Rack, Tower
Number of outlets	8
Outlet type	IEC C13
Battery quantity	6
Connectors	RS-232, USB Type-B
Battery pack connector	Yes
Battery capacity	9 Ah
Battery type	Lead acid VRLA AGM
Battery voltage	12 V
Recharge time	6 h
Input voltage	230 V
Input voltage range	from 110 up to 300 V
Input frequency range	from 40 up to 70 Hz
Output voltage	230 V
Output acceptable voltage range	from 208 up to 240 V
Output frequency	50 Hz
Automatic Voltage Regulation (AVR)	Yes
Waveform type	Full sine wave
AC/DC Transfer time	from 0 up to 0 ms
Cold start	Yes
Protections	Interference filter, Overload protection, Short circuit protection, Surge protection
Noise level	50 dB
Colour	Black
Software	PowerManager II
Supported Operating Systems	Linux, Unix, Windows 7, Windows 7 64bit, Windows 10, Windows 10 64bit, Windows 11
Weatherproof rating	IP20
ICT height	2 U
Dimensions	505 x 438 x 88 mm
Weight	22,9 kg

EAN-13: 5901969447002
CAT. NO: R/2000I/PF1/DF

The information contained in this product data sheet corresponds to the product specifications current as of the date of its preparation. The manufacturer may implement design and technological changes in subsequent versions or batches of the product that do not affect the product parameters specified in this data sheet. The current product specifications are available on the manufacturer's website.