# VIGA PLUS

SLI045011CCT_PW_BLACK

VIGA PLUS LINEAR 600mm 10W/12W/14W 3CCT 230V 120DEG IP20 70x600x28mm BLACK

CCT



| | | | |
|---|---|---|---|
| Power | 10W/12W/14W W | Voltage | 230 V |
| Colour temperature | 2700 / 4000 / 6000 K | Colour of light | CCT |
| Beam angle | 80 ° | Degree of protection (IP) | IP20 |



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

## Technical data

| | |
|---|---|
| Code | SLI045011CCT_PW_BLACK |
| Power | 10W/12W/14W W |
| Nominal current | 87 mA |
| Voltage | 230 V |
| Energy consumption | 14 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power factor | 0.7 |
| Useful luminous flux* | 1750 lm (360°) |
| Luminous flux | 1100/1320/1540 lm (360°) |
| Lamp efficacy | 125 lm/W |
| Colour temperature | 2700 / 4000 / 6000 K |
| Colour of light | CCT |
| Beam angle | 80 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Warranty | 2 years |
| Lifespan | 17000 h |
| (On/Off) | 15000 |
| Housing material | PC |
| Degree of protection (IP) | IP20 |
| Colour | Czarny |
| Dimension (AxBxC) | 70x600x28 mm |
| For use | Inside |
| Assembly method | On the ceiling, Suspended |
| Made in | PRC |
| Other | Removable, CCT switch + Power switch, max 16@line , |

*applies to the LED source used

## Logistics data

| | |
|---|---|
| Bulk packaging | 50 pcs. |
| Gross weight (1 pcs.) | 0.21 kg |

## Related documents

User manual



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu









