

Sterownik LED do taśm RGB

Controller to RGB led strips.

WIFI

30m



- Sterownik LED to trzykanałowy (RGB) odbiornik RF.
- Technologia 2,4GHz, system działa do 30m.
- Odbiornik o stałym napięciu, z trzema wyjściami.
- Pełna kompatybilność z różnymi pilotami, zarówno jedno-, jak i dwukolorowymi, oraz RGB/RGBW.
- Wiele stref można kontrolować oddzielnie lub synchronicznie z nieskończoną liczbą odbiorników w każdej strefie.
- Płynna zmiana kolorów jak i ich przyciemnianie od 0,1% do 100%.
- Jeden sterownik oświetlenia RF może współpracować z dziesięcioma pilotami.
- Jeden odbiornik może przesyłać sygnał z pilota do innego odbiornika w odległości 15 m.
- Całkowita odległość zdalnego sterowania wynosi około 100 m.
- Odbiornik może być sterowany poprzez Wi-Fi – za pomocą aplikacji zainstalowanej na urządzeniach mobilnych z systemami IOS lub Android, podczas pracy ze sterownikiem WiFi-Relay.
- Odbiornik współpracuje ze wzmacniaczami.

- 3 channel RF 2.4G controller, default as RGB type, match with RGB/RGBW remote, create colorful static or dynamic effect.
- Can also be used as dual color temperature or dimming controller, good compatibility.
- Full compatibility with a variety of single color, dual color and RGB/RGBW remote.
- Smooth dimming and switch without any flickering.
- When control RGB lamp, built in 10 mode, include jump or gradual change style.
- Adopt 2.4GHz wireless technology, remote distance up to 30m, can accept up to 10 remote control.
- Auto-transmitting function, one receiver can transmit the signal from the remote to another receiver within 15m, so the remote control distance can be beyond 100m.
- Auto-synchronization function, different receivers can work synchronously when they are controlled by the same remote, under same dynamic mode and same speed.
- Can be WiFi controlled by APP installed on IOS or Android mobile devices while working with WiFi-Relay controller.
- 3CH CV RF controller can connect unlimited number of 3CH CV or CC power repeaters in series or in parallel to expand output power.



PD027293



5908293927293



12V 3x(max 72W)



24V 3x(max 144W)



12-24V



3CH, 6A/1CH



do 30m



0,1% - 100%



20





175 x 45 x 27



100 000



-30/+55



Sterownik współpracuje m.in. z pilotem:

Controller cooperates with pilot:



PD027248

5908293927248

