

## DOWNLIGHTY PODTYNKOWE OKRĄGŁE DOWNLIGHTS ROUND RECESSED MOUNTED



**nextec**

W skład oprawy wchodzi wbudowane lampy LED.

**LED**

A+  
A+  
A  
C  
D  
E

Nie można wymieniać lamp w oprawie.

874/2012

BARWA / COLOUR / LICHTFARBE

1800K  
4000K  
5500K  
8000K  
12000K  
16000K

3000K  
4000K

Im PF CRI

PF028450	5908293928450	630	7W	100-240V AC	300mA	>0,9	> 80	20	120°	4000K	2835	∅ 90x30	95%<1s	30000 ≥35000	-20/+40
PF028467	5908293928467	1440	16W	100-240V AC	300mA	>0,9	> 80	20	120°	4000K	2835	∅120x30	95%<1s	30000 ≥35000	-20/+40
PF028863	5908293928863	1440	16W	100-240V AC	300mA	>0,9	> 80	20	120°	3000K	2835	∅120x30	95%<1s	30000 ≥35000	-20/+40
PF028474	5908293928474	2160	24W	100-240V AC	300mA	>0,9	> 80	20	120°	4000K	2835	∅170x30	95%<1s	30000 ≥35000	-20/+40
PF028870	5908293928870	2160	24W	100-240V AC	300mA	>0,9	> 80	20	120°	3000K	2835	∅170x30	95%<1s	30000 ≥35000	-20/+40
PF028481	5908293928481	3040	32W	100-240V AC	300mA	>0,9	> 80	20	120°	4000K	2835	∅225x30	95%<1s	30000 ≥35000	-20/+40

